Product Code: UC807

HIGH VISIBILITY TROUSERS USER INFORMATION SHEET

EN ISO 20471: 2013+A1:2016





RIS-3279-TOM (Orange only)

EN ISO 20471:2013+A1:2016 Protective Clothing- High Visibility Warning Clothing

High Visibility garments with either yellow or orange background material. Minimum area of fluorescent & reflective material meets class 1. Two bands of retroreflective material around the ankle.

EN 343:2019 Protective Clothing-Protection Against Rain

The indexes indicate the class of the garment. The upper index indicates the resistance to water penetration meets class 3. The lower index indicates the water vapour resistance meets class 1. For the correct protection class of our article, please refer to the sewn in CE label on the article. The test for the readymade garment has not been carried out (the X next to the pictogram).

Warning-Restricted Wearing Time Based on Ambient Working Temperature for a Class 1 Water Vapour Resistance Garment

Ambient Working Temperature (Centigrade)	25°C	20°C	15°C	10°C	5°C
Recommended Maximum Continuous Wearing Time (Minutes)	60	75	100	240	<u>12-12</u>

NOTE: The RET Number (Resistance of Evaporation of a Textile) for a Water Vapour Resistance Class 1 garment is >40. A Restricted Wearing Time as outlined in the table above must be followed.




These garments bear CE marking to demonstrate compliance with EU 2016/425 Personal Protective Equipment Annex II Health & Safety Requirements and the above referenced standards.



These garments bear UKCA marking to demonstrate compliance with UK Legislation – UK2019 SI696 Schedule 35 Regulation 38

The UKCA & EU Declaration of Conformity can be found on the website www.uneekclothing.com

	(cm)	(cm)	
Size	Waist	Height	
S	72-80	170-194	
M	82-90	170-194	
L	92-100	170-194	
XL	102-108	170-194	
2XL	110-114	170-194	
3XL	116-122	170-194	
4XL	124-130	170-194	



AFTERCARE

100% Polyester / PU Coating Max 25 wash cycles









Liability will not be accepted where the care label has been ignored, neglected, defaced or removed. Where relevant, the stated maximum number and type of cleaning cycles are not the only factors that ascertain the lifetime of the garment. The lifetime depends on usage, the work environment, care, storage and where relevant, the number of cleaning cycles.

LIMITATIONS OF USE

The garment should be worn fastened at all times to provide the correct level of protection as stated above. DO NOT modify or alter the garment. This garment must be kept clean to remain effective. Replace if permanently stained, faded or damaged. This garment is made of materials to aid conspicuity. Regular comparison against new garments is recommended. The aftercare instructions must be followed as improper treatment may alter the garment's performance.

This Class 1 trouser will only meet RIS-3279-TOM (Orange Only) when worn with Class 2 upper body clothing

STORAGE

The garment should be worn fastened at all times to provide the correct level of protection as stated above. DO NOT modify or alter the garment. This garment temperature before storing.

DISPOSAL

This garment is suitable for disposal via landfill or municipal waste incineration in accordance with European standards, subject to non-contamination with hazardous substances. We recommend using a specialist workwear disposal/shredding service for disposal to reduce your carbon footprint, where waste is diverted from landfill and recycled. For more information contact your local environmental office.

SIZE RANGE: S to 4XL

EU Notified Body:

INTERTEK Italia S.p.A.

Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy Notified Body. No. 2575

Approved Body:

ITS Testing Services UK Ltd

Centre Court, Meridian Business Park,Leicester, LE19 1WD,United Kingdom Approved Body No. AB0362

For further information contact:

Uneek Clothing Company Ltd Unit 1 & 2, Wellesley Court Apsley Way, London NW2 7HF

Tel: +44(0)845 871 8711 Fax: +44(0)845 871 8712